

AD A 09119

TECHNICAL REPORT RS-CR-80-2

HUMAN ENGINEERING DESIGN CRITERIA FOR MODERN CONTROL/DISPLAY COMPONENTS AND STANDARD PARTS

FINAL REPORT

W. E. Woodson and C. Coburn Man Factors, Inc. 4433 Convoy Street San Diego, CA 92111

В

For

US Army Human Engineering Laboratory Detachment Systems Engineering Directorate US Army Missile Laboratory

May 1980



U.S. ARMY MISSILE COMMAND Redstone Arsenal, Alabama 35898

Approved for public release; distribution unlimited.

SMI FORM 1021, 1 JUL 79 PREVIOUS EDITION IS OBSOLETE

DISPOSITION INSTRUCTIONS

DESTROY THIS REPORT WHEN IT IS NO LONGER NEEDED. DO NOT RETURN IT TO THE ORIGINATOR.

DISCLAIMER

THE FINDINGS IN THIS REPORT ARE NOT TO BE CONSTRUED AS AN OFFICIAL DEPARTMENT OF THE ARMY POSITION UNLESS SO DESIGNATED BY OTHER AUTHORIZED DOCUMENTS.

TRADE NAMES

USE OF TRADE NAMES OR MANUFACTURERS IN THIS REPORT DOES NOT CONSTITUTE AN OFFICIAL INDORSEMENT OR APPROVAL OF THE USE OF SUCH COMMERCIAL HARDWARE OR SOFTWARE.


SECURITY CLASSIFICATION OF THIS PAGE (When Date Entered)

REPORT DOCUMENTATION PAGE	READ INSTRUCTIONS BEFORE COMPLETING FORM			
	. 3. RECIPIENT'S CATALOG NUMBER			
RS-CR-80-2 / AD-909/19/				
4. TITLE (and Subtitle)	Final Technical Report			
Human Engineering Design Criteria for	16 May 1979-16 May 1980			
Modern Control/Display Components and	6. PERFORMING ORG. REPORT NUMBER			
Standard Parts	MFI-80-101 (R)			
7. AUTHOR(e)	8. CONTRACT OR GRANT NUMBER(#)			
W. E. Woodson and C. Coburn	DAAK40-79-C-0145			
9. PERFORMING ORGANIZATION NAME AND ADDRESS	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS			
Man Factors, Inc.				
4433 Convoy Street				
San Diego, CA 92111 11. CONTROLLING OFFICE NAME AND ADDRESS	12. REPORT DATE			
Commander	May 1980			
US Army Missile Command ATTN: DRSMI-RPT	13. NUMBER OF PAGES			
ATTN: DRSMI-RPT Redstone Arsenal AL 35898 14. MONITORING AGENCY NAME & ADDRESS(II different from Controlling Office)	15. SECURITY CLASS. (of this report)			
Commander US Army Missile Command	UNCLASSIFIED			
I ATTN: DRSMI-RS				
Redstone Arsenal, AL 35898	15. DECLASSIFICATION/DOWNGRADING SCHEDULE			
17. DISTRIBUTION STATEMENT (of the ebetrect entered in Block 20, if different fr	om Report)			
18. SUPPLEMENTARY NOTES				
19. KEY WORDS (Continue on reverse side if necessary and identify by block number)			
Review and analysis of control-display re- 1472B for the purpose of updating to refl- component use in military system, equipme	quirements in MIL-STD- ect contemporary hardware			

DD 1 JAN 73 1473 EDITION OF 1 NOV 65 IS OBSOLETE

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)



SUMMARY

This report summarizes work performed under Contract DAAK40-79-C-0145, "Human Engineering Design Criteria for Modern Control/Display Components and Standard Parts".

The purpose of the study project was to develop recommendations for revision of MIL-STD-1472B to update sections dealing with control, display and related human-system manipulative interface requirements.

The study consisted of the following specific tasks:

- a. Examination of compliance levels for various requirements to determine whether certain uses of the mandatory term "shall" is appropriate in terms of its effect on user performance, is necessary in terms of its effect on system performance, and/or is defensible in terms of the basis upon which a requirement was established.
- b. Examination of other military standards and specifications for requirements that appear to conflict with similar requirements in MIL-STD-1472B to determine whether some modification of MIL-STD-1472B and/or other standards or specifications is warranted in order to avoid the necessity of repetitive requests for waiver of one requirement or the other.
- c. Examination of MIL-STD-1472B for its currency with respect to modern component hardware usage in order to expand the Standard where necessary to cover newer products currently in use and/or expected to be in use in the near future.
- d. Examination of specific, quantitative requirements for their correctness under all appropriate applications and recommendation of changes to correct errors, inappropriate applications, and/or to provide appropriate compatibility with similar values in other military documents which may vary slightly due to the fact they were developed at different times or by different individuals having slightly different objectives.

Based on the information developed in the above tasks, specific modifications, additions (and, in a few cases, deletions) to MIL-STD-1472B are recommended. These include not only modifications and additions to written portions of the Standard but also to tabular and illustrative material as well. These recommended changes and additions have been packaged in a separate volume as an addendum to this report. This was done not only to make these

recommendations more convenient for the procuring activity to review but also to make it easier to select and implement the recommendations in order to revise the Standard.

In addition to the detailed paragraph-by-paragraph recommendations relative to modifying contract-specified portions of the Standard which are presented in the separate addendum, suggestions are provided at the end of this report for revision to other parts of the Standard and for additional experimental research needed to produce data to improve the quality of criterion values in support of some requirements. For example, there is a lack of appropriate data upon which to establish female force limits comparable to the male force limits currently defined in the Standard.

Accession For	
NTIS TO SI	-
क्रात १८३	
Utros e sa	
Ju	_
By	
Distant Sign/	1
Avill bullty Codes	
	1
Di. : cial	l
	I
Ι Δ	l
the same of the sa	ı

31

Preface

MIL-STD-1472, "Human Engineering Design Criteria for Military Systems, Equipment and Facilities" is the primary reference for designers when they are dealing with human factors questions relating to design of human-system interface design. It is used not only to provide design guidance but also to measure design compliance.

As hardware state of the art changes it becomes necessary to update MIL-STD-1472, just as with any other hardware standard or specification. In addition, however, there are situations in which certain hardware specifications call out requirements that deal expressly with human engineering questions. In some instances these conflict with similar requirements in MIL-STD-1472 despite a continuing effort to maintain reasonable compatibility between MIL-STD-1472 and these other specifications. The present study has been conducted expressly for the purpose of providing recommendations for an update of MIL-STD-1472B as well as making suggestions for possible modifications of other standards and specifications that deal with the subject of control-display design.

A unique approach of this study has been to utilize the expertise of selected industrial human factors specialists to review proposed changes to MIL-STD-1472B. The purpose of this was to include the needs of military system developers as they attempt to produce products that are compliant with military human engineering requirements. These are the people who must cope not only with military standards and specifications but who often are required to extend the state of the art by utilizing new products and components. Such specialists often are more cognizant of inadequacies of a military standard than are others because they must interpret such requirements in terms of designs that may not have been considered when the requirement was originally written. Thus, although a basic requirement may be valid in principle, the manner in which it is written may not always "fit" a new system, subsystem or component design problem.

The following industrial specialists serving as an Ad Hoc review panel have been extremely helpful in critiqueing proposed modifications to MIL-STD-1472B and suggesting changes to make these recommendations more realistic, applicable and/or pertinent.

Mr. Dick Clark

Dr. James M. Ketchel

Mr. Joseph E. Burke

Ford Aerospace Stanford Research Institute

Vought Cor; .

Mr. William J. Adams

Dr. Arthur Kahn

Mr. Rodney M. Woodward Mr. Eldon T. Winston

Mr. Chuck Geer

Dr. Harry L. Wolbers

Rockwell International

Westinghouse

General Dynamics

RCA Corp.

Boeing Aerospace Co.

McDonnell Douglas Astronautics Co.

In addition, the authors also wish to acknowledge with gratitude the efforts of the members of the Tri-Services Committee for their most helpful guidance and assistance in obtaining documentation for review. The following persons participated:

Mr. Gerald Chaikin

Mr. John Chipser

Mr. Jean M. Ring

Dr. Heber Moore

12

Tri Services Committee Chairman

Army Representative

Air Force Representative

Navy Representative

Table of Contents

	Page	<u> </u>	
INTRODUCTION	6		
RESULTS	8		
RECOMMENDATIONS	10		
APPENDICES			
A - Bibliography	A-1	through	A-12
R - DoD Document References	R-1	through	B-1/4

INTRODUCTION

Study Purpose

1

The purpose of this study was to examine carefully those sections of MIL-STD-1472B (and revision Notices 1 and 2) pertaining to displays and controls, as well as related sections, in order to determine and to recommend modifications necessary to meet the following objectives:

- a. Ensure that the compliance levels of requirements are appropriate in terms of importance, necessity and supportability from a cost-effectiveness point of view.
- b. Determine what serious conflicts appear to exist between related portions of MIL-STD-1472B and other military standards, specifications, or handbooks concurrently in use for military systems development and to recommend appropriate changes, either to this Standard and/or to other documents, in order to remove such conflicts.
- c. Identify areas in which the present Standard is deficient with respect to current and near-future hardware state of the art; i.e., new products that are being used and/or contemplated in new systems and prepare appropriate human engineering requirements with respect to these products to be considered for inclusion in a future revision of this Standard.
- d. Examine carefully all criteria (quantitative data) to determine the correctness or validity of both the older and newer requirements being recommended.

The ultimate product of the above review and analysis is a detailed set of recommended modifications for consideration in a future revision of MIL-STD-1472B. These modifications include such things as simple title or word changes in existing paragraphs; minor re-wording of certain paragraphs or requirements statements to make them applicable to a broader range of design applications and/or to remove certain confusions that could occur due to the manner in which a requirement is stated; the introduction of new or expanded requirements to cover not only new product applications but also to provide appropriate applications of older component concepts that for one reason or another were not addressed in the current statements; and, finally, modifications of or additions to tabular or illustrative criteria and examples provided to support specific criterion statements.

Study Approach

The basic approach to the study has been an iterative process of document review and analysis, current standard material revision, new requirements material development, and revision via an Ad Hoc Committee review cycle. The latter activity is unique in that it has provided a broader intellectual and experience base than normally might exist within the staff of a single research group, e.g., Man Factors, Inc. (MFI).

The review and analysis effort involved a repetitive examination of MIL-STD-1472B from the points of view indicated earlier, i.e., those representative of the following stated objectives:

- a. Compliance level review
- b. Conflicts analysis
- c. New products analysis
- d. Criterion validation analysis

The Ad Hoc review committee was utilized in each of these analyses in order to take full advantage of the broad range of experience represented by committee members. Members were selected on the basis that they were working in the industrial setting and therefore were faced with the specific problem of seeing to it that their company gave appropriate attention to human factors in hardware system development. Such individuals not only were trained human factors specialists, but each represented many years of practical experience in working with the basic human engineering standard for military equipment development, viz., MIL-STD-1472.

The method used to elicit assistance from the Ad Hoc Committee members was for MFI to develop preliminary results for each of the analytic steps and then to submit these to them for their critical review and comment. Therefore the ultimate recommendations submitted in the Addendum to this report actually represent not just the output of the study contractor but, rather, the collective recommendations of a much larger group of specialists highly representative of the military systems development community as a whole.

RESULTS

The primary result is, of course, a fairly comprehensive set of proposed modifications for specific sections plus a few individual paragraphs in other, related sections. The primary sections include the following:

- a. CONTROL/DISPLAY INTEGRATION It was considered important and necessary to expand this section in order to deal with a number of integration problems that either were missing in the present Standard or else were treated so lightly that the particular topics were not representative of the scope and broad applications need of the stated requirement. A good example was the inadequate treatment of the subject of feedback. Another area that was expanded considerably was that of control-display movement relationships because the original material did not adequately address unique aspects of different system applications (e.g., aircraft, automotive systems, ships and submersibles, etc.). A third area that was expanded was the control-display movement ratio section.
- b. VISUAL DISPLAYS The principal areas for expansion in this section related to various display types that were not covered in the original set of requirements and, in particular, new requirements to cover new display products such as LCD's, LED's, plasma and other similar display devices or techniques now in broad use in military systems. Perhaps the most significant expansion, however, occurred in the section dealing with CRT's, not only because the original provided extremely limited guidance but also because the wide use of CRT's presents a major visual display interface design problem for a major share of current military systems.
- c. AUDIO DISPLAYS A considerable expansion of this section was considered necessary just as in the case of the CRT since the original section was minimally representative of the guidance needed to provide adequate audio systems design and development.
- d. CONTROLS The major observation in reviewing and analyzing this section was that the requirements in the original standard were considerably deficient in terms of addressing all the types of controls currently being used in various systems (i.e., aircraft, ships, submarines, automotive vehicles, and other support systems). A special deficiency was noted with respect to keyboards, data pick-off devices, and various foot-operated controls. Although some conflicts were discovered between MIL-STD-1472B and other military standards and specifications in the display area, conflicts appeared to be especially numerous with respect to the controls section. Therefore, this section of the Addendum volume contains a considerable number of changes to expand original requirement

statements and to add new requirements to cover all of the control types not included in the original Standard. Included are a number of suggested illustrations and new tables to provide a more comprehensive and less confusing coverage of all of these controls. It was also found that there was a considerable lack (in the present Standard) of appropriate criteria to accompany the proposed requirements, especially with respect to specifying control resistance limits. A major deficiency occurs because current criteria deal almost exclusively with the male operator and little, if any, equivalent female data apparently is available. Notice 2 for MIL-STD-1472 provides considerable new data on females but not specifically in the area of control resistance.

e. Other Sections - There are, of course, individual requirements relating to operator/maintainer display, control and manipulative interface designs (e.g., handles, fasteners, connectors, etc.) in several "other" sections of MIL-STD-1472B. Minor modifications and/or additions were considered appropriate in several of these. However, there appeared to be no need for modifications of the magnitude described in the above paragraphs.

It should be noted within the context of "results" that, while reviewing MIL-STD-1472B to make sure that all facets of display and control were adequately covered, other deficiencies were observed in several other sections. These should be addressed at some time in the near future to develop recommendations similar to those presently suggested for the display and control sections of the Standard. Deficiencies and possible errors especially noted occur in the sections on GROUND WORKSPACE DESIGN, DESIGN FOR MAINTAINABILITY, SMALL SYSTEMS AND EQUIPMENT, OPERATIONAL AND MAINTENANCE GROUND/SHIPBOARD VEHICLES, AEROSPACE VEHICLE COMPARTMENT DESIGN, and HAZARDS AND SAFETY.

Finally, it is our observation that the present index is highly inadequate and that the overall organization of the Standard leaves much to be desired. Our main concern with respect to the index is that it does not provide a consistent designrequirement perspective. Although the entry words probably are adequate for the experienced human factors specialist, they are less appropriate for the typical engineer or designer--and especially for the various types of designers (i.e., aircraft, automotive, shipboard, etc.). Our major objection to the overall organization of the Standard is that it is not consistent throughout the document and that many of the sections do not follow an expected series of related topics. This has made it extremely difficult in this study to: (1) find pertinent topics; (2) make sure that a proposed modification is compatible with all the other, related, paragraphs; (3) add new material in a logical place (i.e., the material could go into several places); and (4) to minimize redundance because of the arbitrary way in which some related topics are broken up.

RECOMMENDATIONS

Detailed recommendations for modifying specific sections of MIL-STD-1472B are provided in a separate Addendum to this report. This separate document is entitled, "Recommended Modifications to MIL-STD-1472B; Selected Sections on Controls, Displays and Related Hardware".

The present section therefore deals with independent and somewhat general recommendations (over and above those in the Addendum) that should be given serious consideration in the near future.

a. Research Related to Control-Display Requirements

(1) Strength/Force Data - Human strength data and related specifications for control resistance are considered highly suspect in terms of the criteria presented in both this and other military standards and specifications. There is a need, first, to develop data on female strength. Although we have reviewed numerous studies dealing with female strength, comparisons between male and female operators, and isolated applications criteria, the lack of consistency among these studies (not to mention the inappropriateness of the populations studied) lead us to question many of the force criteria currently specified in military documents.

It is therefore recommended that a systematic set of experiments be conducted to address the unique design questions that face system designers. Although laboratory-based studies could provide much of this needed information, it appears desirable that more operationally-oriented experiments be performed. For example, it does little good to provide a table of maximum forces that can be applied to a foot pedal from different knee angle positions. The real problem is pushing a brake pedal, rudder pedals or an accelerator pedal through a specified travel pattern, considering the variables presented by the dynamic characteristics of an auto or truck, a tank, an airplane or other vehicle in the range of operating environments--not to mention the effects of clothing or footware, or the effects of "startle," "fatigue" or other motivational factors. ' "alertness,

Equally questionable are present criteria provided for manual controls, including torque limits for various rotary controls, resistances for levers

of various types, resistances for keyboard keys and common push buttons or thumbwheels. Present criteria provide too simplistic interpretations, i.e., they do not represent differences due to the position of the controls, whether one might be wearing gloves or mittens, whether the control is operated intermittently or repeatedly, and/or whether the control is operated by an index finger, the heel of the hand, and so on. The majority of the present criteria appears to be "best estimated" based on contemporary hardware characteristics.

(2) Special Visual Displays - Research is needed to define further the critical characteristics of several contemporary display devices including CRT's, LCD's and LED's. For example, current criteria relating to selection and use of CRT's are state-of-the-art related. Although this is understandable, recent advances in this state of the art, provide ample evidence that such criteria are "picked up" variously from specific design solutions (in some cases supported by a limited research study) and not from a systematic experimental examination of the key issues that are so important to the designer of a new system.

In the present study, we found considerable disagreement regarding many parameters and criteria for the design and/or selection of CRT's. We utilized the services of a radar expert in producing the recommendations resulting from this study. It was disconcerting to have that individual (with all of his experience) admit that he probably learned more from this exercise than he was able to offer in the way of expertise. Thus, in spite of a considerable improvement in the section over what it was, we feel that a more extensive study should be made of CRT's, including experimental research to derive performance-tested criteria.

(3) Keyboards - We found a very limited amount of information regarding the design and use of keyboards except for such superficial things as key spacing, (questionable) resistance data, and/or keyboard or keypad organization practice.

The principal problem area that appears to need resolution is the confusion regarding: (1) key-pads organized like calculators or telephone arrays; (2) use of alphanumeric keyboard for numeric entry in lieu of a ten-keypad; and (3) considerable confusion about keypad formats with respect to auxiliary keys (e.g., zero, "entry", "clear", etc.). The

only keypad performance data we found support for was the telephone format, yet the general practice for data entry keypads follows traditional calculator format. However in the latter case we find a number of computer magnificturers offering keypads that revert to the telephone format. In our opinion, there may be a better to set than either one, viz., a two-row format using I to an the top row and 6 to '0' in the second row. Although we suspect this may have been evaluated by someone, we could not find any supporting document tion.

It is recommended that additional research be performed to determine all of the "use" and "format" criteria based on operator performance for a wide range of applications. Although it might seem that a change might cause considerable disruption as far as industry is concerned, actually all that really would be required would be changing key caps—unless of course, the keypad format determined best turns out to be a two-by-five or other arrangement.

b. Additional Biomechanical Research — As already noted there is a question as to the validity or credibility of many of the for credibited criteria currently provided in MIL-STD-1472B (as well as in other engineering standards). We have observed, for example, that current force criteria do not reflect the needs of the minitary female. In addition, sany criterian values are based on "experting" rather than an octionmance-related data. And many of the criteria appear purposely to have been made very general due to the complexities involved in taking an application—by-application approach.

It is probably true that in some cases experting may be adequate. 2.t without some better background information (based on performant presearch) of is hard to tell whether expert guesses are adequate on a to A good example of this is the lack of specific data on the forces for weapon or tool trisgers. Interpayation of a wide range of individuals who should know of any research data regarding trigger forces yielded a confusing set of opinions on the subject, but principally the fact that no specific research data are available. Another critical area is the lack of force crit ria associated with special controls such as brake pedals. Recent studies indicate that maximum leg strength has little to lo with a desired terce limit recommendation. Hat is, because of the complex, dynamic nature of brake sage--manual vs. powered, large vs. small vehicles, etc. -a simple admonition to "keep within strength envelopes produced by static laberatory studies" is caticaly madequite for design guidance.

.1

In view of the above it is recommended that additional research be conducted to determine force-related requirements for all of the key applications that MIL-STD-1472B addressed. It is recognized that this recommendation may involve a rather extensive program involving considerable time and expense. But until such reserach is accomplished we will continue to be faced with arguments about the criterion values we are using.

c. General Aviation Display Conflicts - Again as noted earlier, there are major conflicts between the manner in which aircraft instruments are designed and the basic principles espoused by MIL-STD-1472B (as well as most other human engineering guides, handbooks, and research reports). Historically, aircraft controls and displays were somewhat outside the responsibility of human factors specialists at Wright-Patterson except for an advisory role. Many battles occurred between the engineering group responsible for control-display hardware and the human factors groups, and although some human engineering input was slipped-in now and then, general underlying design philosophy resisted any major inroads.

This stalemate has been further amplified by the aircraft instrument manufacturers who typically continue their own traditions. Our initial impulse has been to "fall in line" as has been done in the past. That is, as the present Standard does, to accept the aircraft practices by exception and merely refer to other engineering standards that deal with specific instruments. Upon reflection, however, we realized we cannot in fairness tell one group of designers to follow good human engineering practice and at the same time tell another group to do as they please! Doing so implies that we really do not have solid support for our human engineering principles and criteria.

We therefore recommend that steps be taken to, first, open the subject up to debate. And, second, follow this with a plan for a systematic program for realigning aircraft display philosophies to coincide with recognized human engineering practices. This may, of course, involve some extensive research to support realignment decisions. A good start might be to call a conference of cognizant agencies and persons to review the problem and to develop recommendations for its resolution.

d. Update of Other Sections - Although this study did not address sections of the Standard unrelated to controls and displays (or related manipulative components), our comprehensive reviews of the various sections

emphasized to us that many of them also need revision, particularly those dealing with equipment packaging, consoles, ground systems, maintainability and, most importantly, safety.

e. Separate Human Engineering Standards - The size of the present standard already is rather large and therefore somewhat cumbersome compared to most other standards and specifications. With the proposed modifications resulting from this study it becomes obvious that if they are all accepted and incorporated in a new revision the resulting document will become even more unwieldy. It therefore appears desirable to consider, at some time in the future, some type of separation of requirements into several separate and more manageable standards dealing with specific topic areas (e.g., Controls and Displays, Equipment Packaging, Aircraft Crew Stations, Ground Vehicle Crew Stations, Shipboard Crew Stations, etc.).

.:

APPENDIX A

BIBLIOGRAPHY

The following list of references were utilized during the study to provide guidance in evaluating original requirements in MIL-STD-1472B (and Notices 1 and 2) and preparing modification recommendations.

BIBLIOGRAPHY

- Alden, D. G., et al. <u>Human Factors Principles for Keyboard Design</u> Operation: A Survey Review. Honeywell Microswitch, PPES 70-90.
- Alden, D. G., et al. <u>Human Factors Principles for Keyboard Design & Operation A Summary Review</u>. Honeywell, Inc., Systems Research Center, 26 March 1970 (Prepared for Post Office Bureau of Research & Engineering; P.O. No. PPBS 70-90).
- Alexander, V. D. The Fully Optimized Keyphone. United Kingdom Post Office Research Department.
- Asmussen, E., and Keebol-Nielson, K. Isometric Muscle Strength in Relation to Age in Men & Women. Ergonomics, V2, 167-169, 1962.
- Barnes, J. A. Human Factors in Helicopter Displays. <u>SID Digest</u>, 1972.
- Barnes, M. J. Display Size & Target Acquisition Performance. NWC TP 6006, Naval Weapons Ctr., China Lake, Calif., Jan 1978.
- Bedford, A. D. CRT Considerations in Data Terminal Design. Computer Design, February 1975.
- Bell, G. L. The Effects of Symbol Frequency in Legibility Testing. Human Factors, 9:5, 471-178, 1967.
- Bell, G. L. Studies in Display Symbol Legibility: XV. The Relative Legibility of Leroy and Teletypewriter Symbols. USAF: ESD TR 66-316, 1966.
- Bell, G. L. Studies of Display Symbol Legibility. Part XVI. The Legibility of Teletypewriter Symbols on T.V. Mitre Corp., Bedford, Mass. MTR 888 AD-655-356, 1967.

į

- Bolalek, P. G. and Grumblatt, A. G. A Study to Determine the Adequacy of the Tools and Equipment Used by AF Women in the Craft Skills. AF Inst. of Technology, 1975, WPAFB, Ohio.
- Boucher, B. G., et al. <u>Handbook and Catalog for Instructional Media Selection</u>. Educational Tech Pubs, Englewood Cliffs, N.J., 1973.
- Brebner, J. and Sandon, B. Direction-of-Turn Stereotypes Conflict and Concord. Applied Ergonomics, 7:1, 34-36, 1976.
- Brooks, R. Search Time and Color Coding. <u>Psychonomic Science</u>, 1965, 2, 281-282.

Buckler, A. T. A Review of the Literature on the Legibility of Alphanumerics on Electronic Displays. AMCMS Code 672716.H700011; U.S. Army HEL, Aberdeen Proving Ground, Md., 1977.

Burke, R. W., et al. Optical Characteristics of AC Plasma Panels. Owens-Illinois.

Cahill, M. C. and Carter, R. C. Color Code Size for Searching Displays of Different Densities. <u>Human Factors</u>, 18:3, 273-280, 1976.

Cakir, A., et al. The Visual Display Terminal (VDT) Manual. Inca-Fiej Research Assoc., Washingtonplate 1, D-6100 Darmstadt, Fed Rep of Germany, 1979.

Carr, R. M. The Effects of Color Coding Indicator Displays on Dark Adaptation. <u>Human Factors</u>, 9:2, 175-179, 1967.

Chaikin, G. <u>Stinger Human Factors Engineering Final Report.</u> U.S. Army HEL Tech Memo 25-76, Aberdeen Proving Ground, Md., July 1976.

Chambers, J. B. and Stockbridge, H.C.W. Comparison of Indicator Components and Pushbutton Recommendations. Ergonomics 13:4, 401-420, 1970.

Chapanis, A. and Scarpa, L. C. Readability of Dials at Different Distances with Constant Visual Angle. Human Factors, 9:5, 419-426, 1967.

Christ, R. E. Effects of Pavoff and Probability on Recall of Multi-Symbol Displays. <u>Journal of General Psychology</u>, 80, 81-92, 1969.

Christ, R. E. Review and Analysis of Color Coding Research for Visual Displays. Human Factors, 17:6, 542-570, 1975.

Christ, R. E., and Cerso, G. M. <u>Color Research for Visual Displays</u>. Office of Naval Research, <u>ONR-CR213-102-3</u>, July 1975.

Clare, C. R. Human Factors: A Most Important Ingredient in Keyboard Design. EDN, 20 April, 1976.

Cohen, J. and Dinnerstein, A. J. Flash Rate as a Visual Coding Dimension for Information. (USAF WADC Technical Report 37-64). Wright-Patterson AFB, Ohio, May 1938 (ASTIA Document AD 118-018).

Cohen, E. and Follart, R. L. Accuracy of Interpolation Between Scale Graduations. Human Factors, 12:5, 481-483, 1970.

Conrad, R. and Hull, A. J. The Preferred Layout for Numeral Pata-Entry Keysets. <u>Ergonomics</u>, 11:2, 165-173, 1968.

- Cornog, D. Y. and Rose, F. C. <u>Alphanumeric Characters: A</u>
 Reference Handbook. U.S. Dept. of Commerce, Nat'l Bureau of Stds.,
 1967.
- Cornog, J. R. and Craig, J. C. <u>Keyboards and Coding Systems Under Consideration for Use in the Sorting of U.S. Mail. IEEE Sixth Annual Symposium, Professional Group on Human Factors in Electronics, May, 1965.</u>
- Crawford, A. The Perception of Light Signals: The Effect of the Number of Irrelevant Lights. Ergonomics, 5, 417-428, 1962.
- Crawford, A. The Perception of Light Signals: The Effect of Mixing Flashing and Steady Irrelevant Lights. Ergonomics, 6, 287-294, 1963.
- Crooks, W. H., et al. <u>Television Systems for Remote Manipulation</u>. Proceedings 10th Annual HFS Meeting, October 1975.
- Daniels, R. W. and Graf, C. P. <u>The Influence of Keyset Interlocks on Operator Performance (Phase I Report)</u>. <u>Honeywell, Inc.</u>, <u>Systems Research Center</u>, <u>Roseville</u>, <u>Minn</u>.
- Davis, P. R., and Stubbs, D. A. Safe Levels of Manual Forces for Young Males. Applied Ergonomics, Sept. 1977.
- Davis, S. Computer Data Displays. Prentice-Hall, 1969.
- Deininger, R. L. Human Factors Engineering Studies of the Designs Use of Pushbutton Telephone Sets. <u>Bell System Tech. J. 39</u>, July 1960, 995-1012.
- Deutsch, S. Visual Characteristics Pertinent to Displays. SID Digest, 1973.

. 1

- Deutsch, S. <u>Visual Characteristics Pertinent to Displays</u>. Dept. of Surgery, Rutgers Medical School, Piscataway, N.J. (n.d.)
- Eaton, D. A. and Dittmeier, H.J. <u>Braking and Steering Effort</u> Capabilities of Drivers. SAE Paper 700363, 1970.
- Elias, M. F. Speed of Identification of Televised Symbols as a Function of Vertical Resolution. USAF RADC TR 65-239.
- Ellis, B., et al. The Format and Color of Small Matrix Displays for Use in High Ambient Illumination. Royal Aircraft Est., Farnborough, Hampshire, England.
- Farrell, R. J. and Booth, J. M. <u>Design Handbook for Imagery</u> Interpretation Equipment. Boeing Aerospace Co., Seattle, Wash., D180-19063-1, Dec. 1975.

- FHWA Bulletin HTO-21. Design of New Symbol Signs. U.S. Dept. of Transportation, Federal Highway Administration, 1977.
- Fisher, D. F. Reading and Visual Search. U.S. Army HEL Tech Memo 11-75, Aberdeen Proving Ground, Md., Mar. 1975.
- Foley, P. J. Evaluation of Angular Digits and Comparisons With a Conventional Set. J. Applied Psychology, V40, 178-180, 1956.
- Forbes, T. E., et al. Traffic Sign Requirements. Highway Research Record No. 70 "Night Visibility", (1963 & 1964, 10 Reports (HRB) 1965).
- French, R. L. On-Board Vehicle Ronte Instructions Via Plasma Display Panel. <u>IEEE Trans.</u>, Vol VT-22-36-41, May 1973.
- Fried, C. A. A Human Factors Evaluation of Seven Ditital Readout Indicators. HEL TM 5-60, Aberdeen Proving Ground, Aberdeen, Md., July 1960.
- Gallway, G. R. <u>Keyboards and Data Measures</u>. Masters Thesis, Univ. of Dayton, Dayton, Ohio, 1972.
- Gerathewohl, S. J. Conspicuity of Flashing Signals of Different Frequency and Duration. <u>Journal of Experimental Psychology</u>, 48, 247-251, 1954.
- Gerathewohl, S. J. Conspicuity of Steady and Flashing Light Signals: Variation of Contrast. <u>Journal of the Optical Society of America</u>, 43, 567-571, 1953.
- Gibney, T. K. Legibility of Segmented Versus Standard Numerals: A Review. AMRL-TR-67-116, WPAFB, Ohio, 1967.
- Gibney, T. K. Legibility of Segmented vs. Standard Numerals: The Influence of the Observer's Task. AMRL-TR-68-124, WPAFB, Ohio 1968.
- Giddings, B. J. Alphanumerics for Raster Displays. <u>Ergonomics</u>, 15:1, 65-72, 1972.
- Gilder, J. H., Associate Editor. Focus on Displays, <u>Electronic</u> Design, 26, December 20, 1974.
- Glumm, M. M. The Female in Military-Equipment Design. U.S. Army HEL Tech. Memo 13-76, April 1976.
- Goldstein, D. A., and Lamb, J. C. Visual Coding Using Flashing Lights. Human Factors, 9:5, 405-408, 1967.

Gould, J. D. Visual Factors in the Design of Computer-Controlled CRT Displays. Human Factors, 10:4, 359-376, 1968.

Craham, C. H., et al. <u>Vision & Visual Perception</u>. John Wiley & Sons, 1966.

Green, B. F. and Anderson, L. K. Color Coding in a Visual Search Task. Journal of Experimental Psychology, 1956, 51, 19-24.

Grether, W. F. and Williams, A. C. Speed and Accuracy of Dial Reading as a Function of Dial Diameter and Angular Separation of Scale Divisions. (Chap. in <u>Psychological Research on Equipment Design -- Report No. 19</u>, U.S. Cov't Printing Office, 1947).

Hall, R. J., et al. <u>Human Factors Design Criteria for Transilluminated Displays</u>. Pt. Mugu, <u>Pacific Missile Test Center</u>, 1976.

Harris, W. P., et al. <u>The Design of Characters for the Charactron</u>. Lexington, Massachusetts: M.I.T. Lincoln Laboratory, Technical Report 117, 1956.

Harsh, M.D. Multi-Sensor Displays Two Approaches. <u>Information Display</u>, Sept./Oct. 1966, 24-33.

Hemingway, J. C. and Erickson, R. A. Relative Effects of Raster Scan Lines and Image Subtense on Symbol Legibility on Television. Human Factors, 11:4, 331-338, 1969.

Hertzberg, H.T.E. and Burke, F.E. Foot Forces Exerted at Various Brake-Pedal Angles. <u>Human Factors</u>, 13:5, 445-456, 1971.

Hilgendorf, R. L. An Optimal Hierarchy of Colors for Markers and Signals. Survival and Flight Equipment (SAFE) Association, Proceedings at the Eighth Annual Symposium, Vol. 1, 143-155, September 1970, Las Vegas, Nevada.

:4

Hill, F. W. and Lawrence, A. P. A Review of Research on Maximum Human Pedal Force Capability. SAE Paper for "Efforts Task Force", Feb. 1973.

Hillix, W. A. and Coburn, R. Human Factors in Keyset Design. NEL Research Report 1023, Mar. 1961.

Huddleston, H. F. A Comparison of Two 7 x 9 Matrix Alphanumeric Designs for T.V. Displays. Applied Ergonomics, 5:2, 81-83, 1974.

Hughes, C. L. Variability of Stroke Width Within Digits. J. Applied Psychology, V.45, 364-368, 1961.

Hughes, R. L., et al. <u>Psychological Considerations in the Design of Helmet-Mounted Displays & Sights</u>. AMRI. TR-73-16, WPAFB, Ohio, Aug. 1973

- Johnsen, E. G., and Corliss, W. R. <u>Human Factors Applications in Teleoperator Design and Operation</u>. John W81ey & Sons, Inc., 1971.
- Kanarick, A. F. and Petersen, R. C. Redundant Color Coding and Keeping-Track Performance. <u>Human Factors</u>, 13:2, 183-188, 1971.
- Karim, B. K., et al <u>A Preliminary Study of Maximal Control</u> Force Capability of Female Pilots. Fed Aviation Administration, Report FAA-AM-72-27, July 1972.
- King, R. C., and Semple, C. A., Jr. <u>Electroluminescent Display</u> <u>Legibility Research and Development</u>. The 1970 IDEA Symposium.
- Kinkead, R. Typing Speed, Keying Rates and Optimal Keyboard Layouts. Proc. 19 Annual HFS Meeting, Oct. 1975.
- Kinney, G. C. Studies in Display Legibility. USAF: ESD TR 65-406, 1966.
- Kinney, G. C. and Showman, D. J. Studies in Display Symbol Legibility: XI. The Relative Legibility of Selected Alphanumerics in Two Fonts. USAF: ESD TR 66-116, 1966.
- Kinney, G. C., et al. <u>Studies in Display Symbol Legibility: XII.</u> The Legibility of Alphanumeric Symbols for Digitalized Television. USAF: ESD TR 66-117, 1966.
- Kinney, G. C. and Showman, D. J. Studies in Display Symbol Legibility: XIII. Studies of the Legibility of Alphanumeric Symbols in the BUIC System. USAF: ESD TR-66-302, 1966.
- Klemmer, E. T. Keyboard Entry. Applied Ergonomics, 2:1, 2-6, 1971.
- Konz, S. <u>Maximal Pedal Forces Exertable by Weak Females</u>. Proceedings 21 Annual Meeting HFS, 1977.
- Kroemer, K. H. E. <u>Designing for Muscular Strength of Various</u> Populations. AMRL TR 72-46, WPAFB, Ohio, 1974.
- Landis, D. and Slivka, R. M. Displays for Decision Making. Int'l J. Prod. Res., 10:3, 215-229, 1972.
- Lansdell, H. Effects of Form on the Legibility of Numbers. Canadian J. Psy., V.8, 77-79, 1954.
- Lash, J. D. and Prideaux, G. F. Visibility of Signal Lights: A Digest of Available Test Data Pertinent to the Many Aspects of Present Day Practical Signal Problems. <u>Illuminating Engineering</u>, 38, 481-492, 1943.

Long, G. E. The Effect of Puration of Onset and Cessation of Light Flash on the Intensity-Time Relation in the Peripheral Retina. <u>Journal of the Optical Society of America</u>, 41, 743-747, 1951.

Lutz, M. C. and Chapanis, A. Expected Locations of Digits and Letters on Ten-Button Keysets. J. Applied Psychology, 39:5, 314-317, 1955.

Luxenberg, H. R. and Kuehn, R. L. <u>Display Systems Engineering</u>. McGraw-Hill Book Co., New York, 1968.

Machover, C. Trends in Low-Cost Graphic Display Terminals. SID Digest, 1972.

Markowitz, J. An Investigation of Flashing Visual Indicators: Determining Optimal Flash Rate and Duty Cycle. <u>Human Factors</u>, 1971, 13, in press.

Martin, A. A New Keyboard Layout. Applied Ergonomics, 3:1, 48-51, 1972.

McCormick, E. J. <u>Human Factors in Engineering and Design</u>. McGraw-Hill, Inc., 1976.

Meister, D., et al. <u>Guide to Human Engineering Design for Visual Displays</u>. <u>Bunker-Ramo Corp.</u>, 1969.

Monty, R. A. Keeping Track of Sequential Events: Implications for the Design of Displays. <u>Ergonomics</u>, 16:4, 443-454, 1973.

Morgan, C. T., et al. <u>Human Engineering Guide to Equipment Design</u>. McGraw-Hill Book Co., Inc., New York, 1963.

Mortimer, R. G. <u>Foot Brake Pedal Force Capability of Drivers</u>. Univ. of Mich., Ann Arbor, Mich.

Mortimer, R. G., et al. Brake Force Requirement Study: Driver-Vehicle Braking Performance as a Function of Brake System Design Variables. HSRI Rpt. HuF-6 (NHTSA Contract FH-11-6952), April 1970.

Murrell, K. F. H. <u>Human Performance in Industry</u>. Reinhold Publishing Co., 1965.

Nees, G. Animated Graphics from Display Use for Man-Machine Systems. Advanced Study Inst., Carl Hanser Verlag Munchen, 1972.

Nordgren, B. Anthropometric Measures and Muscle Strength in Young Women. Scandinavian J. Rehab. Med., V.4, 165-169, 1972.

- Oatman, L. C. An Auditory-Visual Interaction Model for Monitoring Army Materiel/Information Displays. U.S. Army MEL Tech Memo 37-76, Aberdeen Proving Ground, Md., Dec. 1967.
- Paul, L. E., et al. A Human Factors Comparison of Two Data Entry Keyboards. IEEE Sixth Annual Symposium, Professional Group on Human Factors in Electronics, May 6-8, 1965.
- Perriment, A. D. and Webster, W. R. Display-Control Relationships With Bisensory Signals. <u>Human Factors</u>, 9:5, 461-470, 1967.
- Pierce, B. F., et al. <u>Human Force Considerations in the Failure of Power Assisted Devices</u>. U.S. DOT, NHTSA, MFI Rpt. 73-105, Dec. 1972.
- Plath, D. W. The Readability of Segmented and Conventional Numerals. Human Factors, 12:5, 493-497, 1970.
- Poole, H. H. <u>Fundamentals of Display Systems</u>. Sparton Books, Inc., 1966.
- Poston, A. M. The Effects of Eliminating Minor Graduations on Dial Reading. U.S. Army HEL Tech Memo 12-77, Aberdeen Proving Ground, Md., Sept. 1977.
- Poularikas, A. D., et al. <u>Legibility Studies of Dot Matrix Displays</u>. Paper based on work supported by the Air Force Flight Dynamics Laboratory, Wright-Patterson Air Force Base, n.d.
- Poulton, E. C. <u>Tracking Skill and Manual Control</u>. Academic Press, New York, 1974.
- Purswell, J. L., et al. A Study of Pilot Control Forces for Female Population Piloting Light Aircraft. Paper presented at 15th Annual Meeting of Human Factors Society, New York, Oct. 1971.
- Radl-Koethe, H. and Schubert, E. Comparative Studies of the Legibility of Light-Emitting Numerals. SID J., May-June, pp 5-10.
- Radlinski, R. W. and Price, J. I. The Brake Pedal Force Capability of Adult Females. National Bureau of Standards, Tech Note 557, Oct. 1970.
- Rees, J. E., and Graham, N. E. The Effect of Backrest Position on the Push Which Can be Exerted on an Isometric Pedal. J. Anat., V.86, 310-319, 1952.
- Remington, R. J., and Rogers, M. Keyboard Literature Survey Phase I: Bibliography. IBM Sys. Dev. Div. TR 29.0042, Feb. 1969.

- Reynolds, R. E., et al. Detection and Recognition of Colored Signal Lights. <u>Human Factors</u>, 14:3, 227-236, 1972.
- Schontz, W. D., et al. Color Coding for Information Location. <u>Human Factors</u>, V.13, 237-246, 1971.
- Sherr, S. <u>CRT Displays: Types and Capabilities</u>. North Hills Electronics, Inc., Glen Cove, New York, 1973.
- Sherr, S. <u>Fundamentals of Display System Design</u>. John Wiley & Sons, Inc., 1970.
- Sherr, S. <u>Large Area Displays</u>. SID Annual Symposium, May 23, 1974.
- Shurtleff, D. A. Legibility Research and Testing of Visual Displays. The Mitre Corp., Bedford, Mass., n.d.
- Shurtleff, D. Design Problems in Visual Displays: Part I; Classical Factors in the Legibility of Numerals and Capital Letters. USAF ESD-TR-66-62, Electronic Sys. Div., L.G. Hanscom AFB, June 1966.
- Shurtleff, D. A. Studies in T.V. Legibility--A Review of the Literature. <u>Information Display</u>, Jan./Feb. 1967, 40-45.
- Shurtleff, D. A., and Owen, D. Studies of Display Symbol Legibility. Part VI, A Comparison of the Legibility of Televised Leroy and Courtney Symbols. ESD-TR-65-136. Part VII. The Legibility of Leroy Symbols on a 945 and 525 Line T.V. System. ESD-TR-65-137. Part IX. The Effects of Resolution, Size and Viewing Angle on Legibility. EDS-TR-65-411. Mitre Corp., Bedford, Mass., 1966.
- Singleton, W. T. Display Design: Principles and Procedures. Ergonomics, 12:4, 519-531, 1969.
- Singleton, W. T., et al (Ed.). The Human Operator in Complex Systems. Taylor & Francis Ltd., London, England, 1969.
- Smith, S. L. Color Coding and Visual Search. <u>Journal of Experimental Psychology</u>, 1962, 64, 434-440.
- Smith, S. L. Color Coding and Visual Separability in Information Displays. Journal of Experimental Psychology, 1963, 47, 358-364.
- Smith, S. L. and Duggar, B. C. Do Large Shared Displays Facilitate Group Effort? Human Factors, June, 1965, 237-244.
- Smith, S. L. and Goodwin, N. C. Alphabetic Data Entry Via the Touch-Tone Pad: A Comment. Human Factors, 13:2, 189-190, 1971.

- Smith, S. L. and Goodwin, N. C. Blink Coding for Information Display. Human Factors, 13:3, 283-290, 1971.
- Smith, S. L. and Thomas, D. W. Color Versus Shape Coding in Information Displays. <u>Journal of Applied Psychology</u>, 1964, 48, 137-146.
- Snyder, H. L. The Sensitivity of Response Measures of Alphanumeric Legibility to Variations in Dot Matrix Display Parameters. Human Factors, 1979, 21(4), 457-471.
- Sobel, A. <u>Display Quality and Human Perception</u>. SID Annual Symposium, May 22, 1974.
- Sobel, A. A Survey of Electronic Numeric Indicator Devices. SID Digest, 1972.
- Stevens, M. E. Recent Advances in Display Media: Volume II. Technical Publishing Co., 825 S. Barrington Ave., Los Angeles, Calif.
- Stokes, J. W. Man/System Requirements for Weightless Environments. MSFC Std 512A, NASA, Marshall Space Flight Ctr, 1976.
- Stoudt, H. W., et al. <u>Vehicle Handling: Force Capabilities for Braking and Steering</u>. <u>Harvard School of Public Health, Guggenheim Ctr for Aviation Health & Safety (NHTSA Contract FH-11-6910)</u>.
- Stowell, H. R., and Poston, A. M. A Human Factors Evaluation of a Vertical-Scale Instrument Display System for the OV-ID Aircraft. U.S. Army HEL Tech Memo 4-77, Aberdeen Proving Ground, Md., Jan. 1977.
- Teichner, W. H., et al. <u>Color Coding in Visual Displays</u>. Final Report, ONR-CR-213-102-4, May 1977.
- Tynan, P., and Sekuler, R. <u>Sourcebook of Factors Affecting Information Transfer from Visual Displays</u>. (Navy Contract N61756-76-M-5961), 1978.

11

- VanCott, H. P., and Kinkade, R. G. (Eds.). Human Engineering Guide to Equipment Design. U.S. Gov't Printing Office, 1972.
- Vartabedian, A. G. Developing a Graphic Set for Cathode Ray Tube Display Using a 7 x 9 Dot Pattern. <u>Applied Ergonomics</u>, 4:1, 11-16, Mar.1973.
- Variabedian, A. G. The Effect of Symbol Generation Method, Slanting, Dot Matrix Size, and Dot Geometry on Legibility. Bell Telephone Laboratories, Holmdel, New Jersey, n.d.

- Vartebedian, A. G. Effects of Parameters of Symbol Formation on Legibility. Info Display, 7:5, 23-26, May, 1970.
- Vartabedian, A. G. Legibility of Symbols on CRT Displays. Applied Ergonomics, 2:3, 130-132, 1971.
- Webb, S. A Comparative Study of Six Keyset Entry Units. NEL R&D Rpt. 902, Feb. 1959.
- Williams, C. M. Legibility of Numbers as a Function of Contrast and Illumination. <u>Human Factors</u>, 9:5, 455-460, 1967.
- Woodson, W. E., and Conover, D. W. <u>Human Engineering Guide</u> for Equipment Designers. University of California Press (2 Ed.), Berkeley, Calif., 1964.
- Wulfeck, J. W., et al. <u>Vision in Military Aviation</u>. WADC TR 58-309, WPAFB, Ohio, Nov. 1958.
- ---- Anthropometric Source Book Volumes 1-3 (Anthrop). NASA Reference Pub. 1024, 1978 (by Webb Assoc.).
- ---- Applied Ergonomics Handbook. <u>Applied Ergonomics</u>, 1:2, 95-106, Chap 4, 1970.
- ---- Data Display Programming. NASA CR-1107, Wash., D.C., Sept. 1968 (Prep. by Wolf Research & Development Corp.).
- ---- Human Factors Engineering. AFSC Design Handbook DH 1-3, Series 1-0, Dept. of the Air Force, Hqs Aeronautical Systems Div. WPAFB, Ohio.
- ---- Shuttle Remote Manned Systems Requirements Analysis. Martin Marietta Corp. Final Report MCR-73-337, Vol. II, 1973.
- ---- Visual Information Display Systems: A Survey. NASA SP-5049, Office of Technology Utilization, 1968.
- ---- Visual Information Displays -- A Survey. NASA SP 5049, Supt. of Docs., U.S. Printing Office (Auerbach Corp. 1968).
- ----- Handbook of Human Engineering Data for Designers. Tufts College Inst. of Appl Exp Psychology. Tech Rpt No. SDC 199-1-1. Special Devices Center, Nav Exos P-643.
- ---- Interactive Graphics. U.S. Army HEL, Aberdeen Proving Grounds, Md.
- the Display Techniques Branch, Eng. Div. Rome Air Development Center, AFSC, Criffiss AFB, New York.

APPENDIX B

DEPARTMENT OF DEFENSE DOCUMENT REFERENCES

The following documents were reviewed and analyzed for potential conflicts with MIL-STD-1472B. Arthough a considerable number of additional documents were also reviewed, documents listed here were the ones actually containing human-system interface requirements-making this list weful for anyone responsible for maintaining continued compatibility between MIL-STD-1472B and other military standards and specifications.

MIL-STD-12C Abbreviations for use on Drawings, Specifications, Standards and in Technical Documents

MIL-STD-101B Color Code for Pipelines and for Compressed Gas Cylinders

MIL-STD-104B Limits for Electrical Insulation Color

MIL-STD-129H Marking for Shipment and Storage

MIL-STD-188C Military Communication System Technical Standards

MIL-STD-195 Marking of Connections for Electric Assemblies

MIL-STD-203F Aircrew Station Controls and Displays: Assignment, Location, and Actuation of, for Fixed Wing Aircraft

MIL-STD-250D Aircrew Station Controls and Displays for Rotary Wing Aircraft

MIL-STD-411D Aircrew Station Signals

MIL-STD-415D Test Provisions for Electronic Systems and Associated Equipment, Design Criteria for

MIL-STD-450B Signs for Contaminated or Dangerous Areas

MIL-STD-681B Identification Coding and Application of Hook Up and Lead Wire

MIL-STD-783C Legends for Use in Aircrew Stations and on Airborne Equipment

MIL-STD-808 (USAF) Finishes, Protective, and Codes, for Finishing Schemes for Ground and Ground Support Equipment


MIL-STD-850B Aircrew Station Vision Requirements for Military Aircraft

MIL-STD-882A System Safety Program Requirements

MIL-STD-884C Electronically or Optically Generated Displays for Aircraft Control and Combat Cue Information

MIL-STD-1132A Switches and Associated Hardware, Selection and Use of

MIL-STD-1179A Lamps, Reflectors and Associated Signaling Equipment for Military Vehicles



MIL-STD-1180 (AT) Safety Standards for Military Ground Vehicles

MIL-STD-1247B Markings, Functions and Hazard Designations of Hose, Pipe, and Tube Lines for Aircraft Missile, and Space Systems

MIL-STD-1280 Keyboard Arrangements

MIL-STD-1333A Aircrew Station Geometry for Military Aircraft

MIL-STD-1343 (NAVY) Glossary of Terms for Electronic and Weapons Control Interface Functions (Naval Ship Combat Systems)

MIL-STD-1348 Knobs, Control Selection of

MIL-STD-1353A Electrical Connectors and Associated Hardware, Selection and Use of

MIL-STD-1365 General Design Criteria for Handling Equipment Associated With Weapons and Weapon Systems

MIL-STD-1515A Fastener Systems for Aerospace Applications

MIL-STD-1555 Aircrew Station Displays and Associated Equipment, Definitions of

MS 21027 Switch, Toggle, Positive Break--Level Lock--Miniature, Toggle Sealed, Solder Lug, Double Pole, .469 Mounting Bushing

MS 21359 (USAF) Knobs-Control, Aluminum Alloy (Round, Concentric, Pointer, Spinner, Slotted, Bar, Locking Shaft Hole, and Knob Locks)

MS 21385 (USAF) Knobs-Tactile Series, Illuminated and Non-Illuminated

MS 25010 Light, Panel - Plastic Plate Lighting

MS 25165 Knob, Pointer, Illuminated, Small

MS 25166 Knob, Pointer, Illuminated

MS 25167 (ASG) Knob, Round, Small

MS 25168 (ASG) Knob, Round

MS 25169 (ASG) Knob, Bar, Small

MS 25170 (ASG) Knob, Bar

MS 26521 Handles, Control, Aircraft Landing Gear

MS 26523 (ASG) Handles, Control, Aircraft Fire Extinguisher

MS 27202 (ASG) Indicator, Position, Landing Gear, Symbol-Indicating, Integrally Lighted

MS 28112 (WEP) Instrument, Basic Standard Arrangement for Fixed Wing Aircraft

MS 33558 (ASC) Numerals and Letters, Aircraft Instrument Dial, Standard Form of

MS 33585 (ASG) Pointers, Dial, Standard Design of Aircraft Instrument

MS 33634 Instrument Arrangement, Engine, Standard, Basic for Fixed and Rotary Wing Aircraft

MS 33636 (ASC) Measurement, Units of, For Aircraft Instruments

MS 33739 Aircraft Markings, Servicing and Precautioning

MS 33785 Instrument Arrangement, Flight, Standard, Basic for Fixed and Rotary Wing Aircraft

MS 51113 Switch, Vehicular Lights: 24 Volt DC; (Waterproof)

MS 51399 (AT) Instrument Cluster: Automotive, Tactical Wheeled Vehicle, (W/O Air)

MS 53003 (AT) Instrument Cluster: Automotive, Tactical Wheeled Vehicle, 5 to 10 Tons Capacity (With Air)

MS 87017 Switches (Arrangement and Functions) Grip Assembly, Cyclic Controller, For Installation in Helicopters

MS 91522 Knob, Control, Crank, Metal

MS 91524 Knobs Control, Short Bar, Metal and Plastic

MS 91525 Knobs, Control, Bar, Metal

MS 91528 Knobs-Control, Plastic (Round, Concentric, Pointer, Spinner, Spinner Slip Clutch, Bar, Tactile, Knob Lock Pointer, and Knob Locks)

MS 91531 Knobs, Control, Round, Plastic (With Fluted Grip)

MIL-A-15303N (SHIPS) Audible Signals: Alarms, Bells, Buzzers, Horns, Sirens, and Electronic Shipboard

MIL-A-25719A (USAF) Accelerometer, Aircraft, Pilot's Warning, Type MA-1



MIL-A-MIL-A-25165B (ASG) Aircraft Emergency Escape System, Identification of

MIL-B-8568B Binoculars, Prismatic, Hand-Held (For Aeronatuical Use) (7 x 50 and 6 x 42 (Wide Field))

MIL-B-8584C Brake Systems, Wheel, Aircraft, Design of

MIL-B-17311 (SHIPS) Binocular, Hand-Held, For Marine Use

MIL-B-23306A (SHIPS) Binocular, Ship, 20-Power, and Accessories

MIL-B-46334C (MU) Binocular, Infrared: M18

MIL-C-25050A (ASG) Colors, Aeronautical Lights and Lighting Equipment, General Requirements For

MIL-C-60618B (MU) Counter, Rotating, Mechanical, Direct Drive: 8587543 (3200 MIL Reset)

MIL-C-6781B (ASG) Control Panel: Aircraft Equipment, Rack or Console Mounted

MIL-C-8779D Colors, Interior, Aircraft, Requirements for

MIL-C-25969B (USAF) Capsule Emergency Escape Systems, General Requirements For

MIL-C-29025A (TD) Communication Systems For Training Devices General Specification For

MIL-C-87952 Counter, Electronic, Digital Readout 18 GIGAHERTZ (GHZ CONTINUOUS WAVE (CW))

MIL-D-28728/1A Dial, Control, Multiturn Counters 15-Turn Counter, Concentric

MIL-D-28728/2A Dials, Control, Multiturn Counters 10-Turn Counter, Concentric (1.250 Inches High)

MIL-D-28728/3A Dial, Control, Multiturn Counters 10-Turn Counter, Concentric (1.810-inch Diameter)

MIL-D-28728/4 Dial, Control, Multiturn Counters 10-Turn Counter, Concentric

MIL-D-28728/5 Dial, Control, Multiturn Counters 10-Turn Counter, 3-Digit

MIL-D-28728/6 Dial, Control, Multiturn Counters 10-Turn Counter, 3-Digit, Illuminated

MIL-D-28728/7 Dial, Control, Multiturn Counters 100-Turn Counters, 4-Digit

MIL-D-28728/8 Dial, Control, Multiturn Counters 10-Turn Counter, Concentric (.875 inch Diameter)

MIL-F-8785B (ASG) Flying Qualities of Piloted Airplanes

MIL-F-18372 (Aer) Flight Control Systems: Design, Installation and Test of, Aircraft (General Specification tor)

MIL-C-81704 Glass, Aircraft Instrument, Highting Wedge and Cover

MIL-H-8810B Handles, Control, Aircraft

.1

MIL-H-46855B Human Engineering Requirements for Military Systems, Equipment and Facilities

MIL-H-83511 Headsct-Microphone and Headset-Electrical (Medium Noise Attenuation, Hearing Protective), General Specification for

MIL-I-25931B (ASG) Indicator, Position, Landing Gear, Symbol-Indicating, Integrally Lighted

MIL-I-27197B (USAF) Indicator, Airspeed, Mach Number and Maximum Allowable Speed

MIL-I-38139C (USAF) Indicator, Vertical Velecity AAU-18/A, Integrally Lighted

MIL-I-81387A (AS) Indicators, Liquid Oxygen Quantity

MIL-I-81400 (AS) Instruments, Aircraft, Ceneral Specification For

MIL-I-81663 (AS) Indicators, Built-In-Fest (BIT), General Specification For

MIL-I-82356 Instruments, Simulated, For Arroraft Training Devices; General Specification For

MIL-I-83287/2A Indicators, Fault Locating, Flag Indicating, Electrical Reset

MIL-I-83287D Indicators, Fault Locating, General Specification For

MIL-I-83287/4 (USAF) Indicators, Fault Locating, Flag Indicating, Mechanical Reset

MIL-I-83452A Indicator, Japo Type, General Specification For

MIL-K-3926B Knobs, Control (For Use With Electronic, Communications, and Allied Equipment)

MIL-K-48213 (MU) Knob, Setting

MIL-K-50889 (MU) Knob, Setting

MIL-K-25049B (ASG) Knobs, Control, Equipment, Aircraft

MIL-L-3976B Lights, Marker, Clearance (Service and Blackout)

MIL-L-5057E Lights, Instrument, Individual, General Specification For

MIL-L-5667B (USAF) Lighting Equipment, Aircraft Instrument Panel, General Specification For Installation of

MIL-L-6503H Lighting Equipment, Aircraft, General Specification For Installation of

MIL-L-7961B Lights, Indicators, Press to Test

MIL-L-18276C Lighting, Aircraft Interior, Installation Of

MIL-L-25142A Luminescent Material, Clourescent

MIL-L-25467D Lighting, Integral, Red, Aircraft Instrument, General Specification For

MIL-L-27160C (USAF) Lighting, Instrument, Integral, White General Specification For

MIL-L-006730C (AS) Lighting Equipment; Exterior, Aircraft (General Requirements for)

MIL-M-5755B Mirror, Rearview, Nonmagnetic, General Requirements For (For Aeronautical Use)

MIL-M-18012B Markings For Aircrew Station Displays Design and Configuration Of

MIL-M-60172 (MU) Manual Keyboard: 10526191

MIL-M-8555B Missiles, Guided: Design and Construction General Specification For

MIL-M-10304E Meters, Electrical Indicating, Panel Type, Ruggedized, General Specification For

MIL-M-11745B (ME) Marking and Labeling of U.S. Army Marine Craft

MIL-M-1321A (SigC) Marking of Electronic Items

MIL-M-16034A Meters, Electrical-Indicating (Switchboard and Portable Types)

MIL-M-46728B Mirror Assembly, Rearview: Automotive, Exterior Mounting

MHL-M-60903 (MU) Marking of Electrical Wires and Cables

MIL-N-85005A (AS) Navigation Display Set, AN/ASN-124

MIL-P-514D Plates, Identification, Instruction and Marking, Blank

MIL-P-7788E Panels, Information, Integrally Illuminated

MIL-S-22710/11D Switches, Rotary (Printed Circuit) (Thumbwheel Switch Assembly, Integral Bezel, Nonsealed, Illuminated or Nonilluminated), Style SRPCH

MIL-S-9320C Signal, Warning, Audible, For Headset, Type MA-1

MIL-S-22885/9J Switch, Push Button, Illuminated, 4-Lamp, Solid Mount, (Modular Constructed)

MIL-S-22885/10F Switch, Push Button, Illuminated Indicator Light For, Modular, 4-Lamp

MIL-S-22885/12D Switch, Push Button, Illuminated, Cap, Color Filter

MIL-S-22885/58C (EC) Switch, Push Button, Illuminated, 2-Lamp, Solid Mount, 3 Amperes, Unsealed

MIL-S-22885/59A (EC) Switch, Push Button, Illuminated, 2-Lamp, Lens Arrangements For

MIL-S-22885/6/E Swtiches, Push Button, Illuminated, 4-Lamp, 0.75 Square, 7 Amperes, Electronagnetic Interference Shielded

MIL-S-22885/70B (EC) Switch, Push Button, Illuminated Color Filter

MIL-S-22885/80C (EC) Switch, Push Button, Illuminated, 4-Lamp, Solid Mount, RFI Shielded, Moisture Sealed, High Impact Shock Resistant

MIL-S-24187/6 (SH) Switch Assemblies, Linear Movement, Manual and Remote Operation, Snap-Action, Style SLS

MII-S-24187D (SH) Switch Assemblies, Linear Movement, Manual and Remote Operation, General Specification For

MILTS-58095 (AV) Seat System: Crashworthy, Non-Ejection, Aircrew, General Specification For

MIL-S-81771A (AS) Seats; Aircrew, Adjustable; Aircraft General Specification For

MIL-T-23991E Training Devices, Military; General Specification For MIL-T-9906A Tape, Aircraft Tubing Identification Marker (Non-Corrosive, Heat, Cold, and Solvent Resistant)

FED SPEC GG-G-66b Gage, Pressure, Dial Indicating

FED SPEC GG-G-76D Gages, Pressure and Vacuum, Dial Indicating (For Air, Steam, Oil, Water, Ammonia, Chloro-Fluoro Hydrocarbon Gases, and Compressed Gases)

FED SPEC UU-D-171B Decals

FED STD No. 3 Colors, Aeronautical Lighting

FED STD No. 186 Marking of Valves, Fittings, Flanges, and Unions Used in Nuclear Reactor Systems

FED TEST METHOD STD No. 406 Plastics: Methods of Testing

AIR STD 10/2E Units of Measurement

AIR STD 10/6D Numerals and Letters for Aircrew Station Displays

AIR STD 10/8C Vertical Speed Indicators

AIR STD 10/9A Machmeters

AIR STD 10/12E Operation of All Controls and Switches at Aircrew Stations in Fixed Wing and Rotary Wing Aircraft

AIR STD 10/14D Grouping of Electrical Swtiches in Fixed Wing Aircraft

AIR STD 10/15K Location and Actuation of Aircrame Controls in Fixed Wing Aircraft

AIR STD 10/19E Illumination of Aircrew Stations

AIR STD 10/20F Location, Actuation and Shape of Airframe Controls for Rotary Wing Aircraft

AIR STD 10/23D Emergency Control co; our Schemes in Fixed Wing and Rotary Wing Aircraft

AIR STD 10/25F Location and Arrangement of Engine Instruments in Aircraft

AIR STD 10/30F Aircrew Station Warning Cautionary and Advisory Signals in Fixed Wing and Rotary Wing Aircraft

AIR STD 10/38B Principles of Presentation of Information

AIR STD 10/40A Location and Actuation of Lift/Thrust Controls for VTOL Aircraft Other Than Helicopters

AIR STD 10/41A Airspeed Indicators

AIR STD 10/42B Attitude Indicators

AIR STD 10/47 Nomenclature in Aircrew Stations

AIR STD 51,2A Emergency Markings

AIR STD 10/53B External Vision From Aircrew Stations

AIR STD 10/57 Vertical Scale Flight Instruments

AlR STD 11/1F Aircraft Servicing/Hazard Markings

AIR STD 65/3B Marking of Airfield Obstructions

NAT STD 3109 Symbol Marking of Aircraft Servicing Points

NAT STD 3153 Aircraft Navigation and Auti-Collision Lights

NAT STD 3154 Aircraft Formation Lights

NAT STD 3158 Day Marking of Airfield Runways and Taxiways

NAT STD 3217 Operation of Controls and Swtiches at Aircrew Stations

NAT STD 3218 Location, Actuation and Shape of Engine Controls and Swtiches for Fixed Wing Aircraft

NAT STD 3219 Location and Grouping of Electrical Swtiches in Fixed Wing and Rotary Wing Aircraft

NAT STD 3220 Location, Actuation and Shape of Airframe Controls for Fixed Wing Aircraft

NAT STD 3221 Automatic Flight Control System (AFCS) in Aircraft - Design Standards and Location of Controls

NAT STD 3224 Aircrew Station Lighting

NAT STD 3225 Location, Actuation and Shape of Airframe Controls for Rotary Wing Aircraft

NAT STD 3230 Emergency Markings on Aircraft

NAT STD 3322 Turn and Slip Indicators

NAT STD 3329 Numerals and Letters in Aircrew Stations

NAT STD 3341 Emergency Control Colour Schemes

NAT STD 3346 Day Marking of Airfield Obstructions

NAT STD 3359 Location and Arrangement of Engine Instruments in Aircraft

NAT STD 3449 Vertical Scale Tape Indicating Flight Instruments

NAT STD 3640 Attitude Director Indicators

NAT STD 3451 Integrated Machineter and Airspeed Indicator

NAT STD 3593 Numbering of Engines and Their Associated Controls and Displays in Aircraft

NAT STD 3643 Coating, Reflection Reducing For Glass Elements Used in Aircraft Station Displays

NAT STD 3692 Location and Actuation of Thrust Vector Controls for VSTOL Aircraft Other Than Rotary Wing Aircraft

NAT STD 3675 Symbols On Land Maps, Aeronautical Charts and Special Naval Charts

NAT STD 3705 Principles of Presentation of Information in Aircrew Stations

NAT STD 3711 Airfield Marking and Lighting Colour Standards

NAT STD 3741 Horizontal Situation Indicators

1 9

HEL STD S-2-64A Human Factors Engineering Design Standard For Vehicle Fighting Compartments

HEL STD S-2-65 Human Factors Engineering Design Standard for Missile Systems and Related Equipment

HEL STD S-5-65 An Evaluation Guide for Army Aviation Human Factors Engineering Requirements

HEL STD S-6-66 Human Factors Engineerin g Design Standard for Wheeled Vehicles

HEL STD S-7-68 Human Factors Engineering Design Standard for Communication Systems and Related Equipment

TECH MEMO 21-62 Manual of Standard Practice for Human Factors in Military Vehicle Design

MIL-HDBK 141 Optical Design

MIL-HDBK 255 (AS) Nuclear Weapons Systems, Safety, Design and Evaluation Criteria For

MIL-HDBK 600 Guidelines for Identification, Marking, Labeling, Storage, and Transportation of Radioactive Commodities

MIL-HDBK 759 Military Standardization Handbook, "Human Factors Engineering Design for Army Materiel", Mar 1975

Design Handbook, Series 1-0 General, AFSC OH 1-6, "System Safety" Hqs Air Force Systems Command in cooperation with National Aeronautics & Space Administration - WPAFB, Ohio

AFSC Design Handbook DH 2-2, Series 2-0, Aeronautical Systems - "Crew Stations & Passenger Accommodations"

AFSCM 80-1 (HIAD) "Handbook of Instructions for Aircraft Design", Andrews AFB, Wash., D.C.

Engineering Design Handbook, AMCP 706-134, "Maintainability Guide for Design", Hqa U.S. Army Materiel Command, Wash., D.C.

AFSC Manual 80-6 "Handbook of Instructions for Ground Equipment Design" (HJAGD) - Mga AFSC, Andrews AFB, Wash., D.C.

AFSC DH 1-3, Design Handbook Series 1-0, General "Personnel Subsystems", Hqs AFSC, WPAFB, Ohio

IES Lighting Handbook (6th Ed), Illum Eng Soc., New York, N.Y.

AEROSPACE STANDARD AS 271A Aircraft Position Lights

AEROSPACE RECOMMENDED PRACTICE ARP 493 Knobs, Control 'ircraft, Recommended Design

AEROSPACE RECOMMENDED PRACTICE ARP 498A Design, Layout, Crtieria-Plastic Integrally Lighted Panels

SAE J585e Motorcycle Turn Signal Lamps

SAE J585e Tail Lamps (Rear Position Lamps)

SAE J586d Top Lamps

SAE J578c Color Specification for Electric Signal Lighting Devices

SAE J588e Turn Signal Lamps

SAE J593e Backup Lamps

SAE J595b Flashing Warning Lamps for Authorized Emergency, Maintenance and Service Vehicles

SAE J589b Turn Signal Switch

SAE J914a Side Turn Signal Lamps

FMVSS No. 101 Control Location, Identification and Illumination-Passenger Cars, Multipurpose Passenger Vehicles, Trucks and Buses

FMVSS No. 102 Transmission Shift Lever Sequence, Starter Interlock, and Transmission Braking Effect--Passenger Cars, Multipurpose Passenger Vehicles, Trucks, and Buses

ANSI C83.1 EIA Standard Colors for Color Identification and Coding

ANSI PH7.6 American National Standard Method for Calculation and Preparation of Projected-Image Size and Projection Distance Tables for Audio-Visual Projectors

ANSI S3.2 USA Standard Method for Measurement of Monosyllabic Word Intelligibility

ANSI S3.5 American National Standard Methods for the Calculation of the Articulation Index

ANSI X3.32 American National Standard Graphic Representation of the Control Characters of American National Standard Code for Information Interchange

ANSI X4.14 American National Standard Alphanumeric Keyboard Arrangements Accommodating the Character Sets of ASCII and ASCSOCR

ANSU Z53.1 American National Standard Safety Color Code for Marking Physical Hazards

X3/TR=1=77 American National Dictionary for Information Processing

MSFC Design Standard 512A "Man/System Requirements for Weightless Environments", NASA Marshall Space Flight Center

NAVSHIPS 94324 "Maintainability Design Criteria for Designers of Shipboard Electronic Equipment", U.S. Gov't Printing Office, Wash., D.C.

